

## Scapa 1100

### Cellulose Adhesive Tape

#### DESCRIPTION

Scapa 1100 is a clear release coated cellulose film coated with a rubber/resin solvent based adhesive, with 47µm total thickness and recommended for general packaging and splicing applications.

#### APPLICATIONS

- Not suitable for use in conditions of high humidity.
- Suitable for general splicing industrial applications with exception of siliconised substrates.
- Suitable for a variety of domestic packaging and sealing applications at home, at school or in the office.

#### PRODUCT BENEFITS

- High tack.
- High clarity.
- Hand tearable.
- Easy unwind.

#### TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesion to Steel	2.4	N/cm	AFERA 5001
Elongation at Break	22	%	AFERA 5005
Tensile Strength	29	N/cm	AFERA 5004
Total Thickness	0.043	mm	AFERA 5006

## STANDARD PRESENTATIONS

- Colours: Amber, Note: from light amber to dark amber, due to natural rubber adhesive.
- Core: 76 mm Scapa branded cardboard core
- Packaging: Sleeve pack (for 12 to 25mm) – Concertina (38 and 50mm)
- Roll Length: 66m
- Roll Width: 12, 15, 19, 25, 38 and 50mm

## RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes.

Cellulose based products are sensitive to heat, moisture and storage conditions. When stored in their original carton at recommended conditions of +23°C and 50% relative humidity, the best usage date will be within 6 months from the date of shipment.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.