

Scapa 2715

PVC Lane Marking Adhesive Tape - 0.13mm

DESCRIPTION

Scapa 2715 is a 0.13mm general-purpose self-extinguishing soft PVC tape, which uses an aggressive pressure sensitive rubber-based adhesive system. It combines good mechanical strength and abrasion resistance with excellent conformability for use in colour coding and lane marking applications.

APPLICATIONS

- Colour coding.
- Flooring and lane marking.
- General splicing.

PRODUCT BENEFITS

- Good resistance to abrasion, corrosion and moisture.
- Suitable for indoor and protected outdoor environments.
- Excellent conformability.
- Environmentally friendly technology.
- Conforms to European Directive 2000/53 EC (lead, chromium VI, mercury, cadmium free).
- Continuous Temperature +60°C.

Accreditation:

2715 conforms to the technical performance requirements of BS4J10

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesion on Backing	1,5	N/cm	CEI EN 60454
Adhesion to Steel	1,5	N/cm	CEI EN 60454
Elongation at Break	150	%	CEI EN 60454
Flammability	Self extinguishing	-	CEI EN 60454
Nominal Thickness	0,13	mm	CEI EN 60454
Tensile Strength	18	N/cm	CEI EN 60454

STANDARD PRESENTATIONS

- Roll Length: 33 mètres
- Roll Width: 38, 50, 75 et 100mm
- Core: Tube carton de 76 mm
- Packaging: Film rétractable
- Colours: Blanc, Bleu, Gris, Noir et Rouge

RECOMMENDATIONS

Rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. The storage temperature should be between +10°C and +25°C. Use within 24 months of receipt

The tape should be applied with sufficient pressure to ensure an optimum bonding and prevent flagging effects.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants