

Scapa 7019

BOPP Filament Reinforced Packaging Adhesive Tape

DESCRIPTION

Scapa 7019 is a 28 μ bi-axially oriented polypropylene film reinforced with monodirectional glass filaments coated with a rubber based adhesive system, with 130 μ total thickness. Recommended for general bundling, packaging and palletising applications.

APPLICATIONS

- Suitable for a variety of medium to heavy duty domestic packaging and sealing applications at home, in the office and in a wide variety of industries.
- Palletising of boxes.
- Bundling.
- Box reinforced sealing.

PRODUCT BENEFITS

- Continuous temperature resistance: +50°C
- Solvent free
- Reduced stretching.
- High tensile strength.
- High tack.

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesion to Steel	7	N/cm	AFERA 4001
Elongation at Break	10	%	AFERA 4005
Tensile Strength	250	N/cm	AFERA 4004
Total Thickness	0.130	mm	AFERA 4006

STANDARD PRESENTATIONS

- Colours: Translucent
- Core: 76mm cardboard core
- Packaging: Concertina
- Roll Length: 50 metres
- Roll Width: 12, 15, 19, 25, 38 and 50mm

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C. Under these conditions, the storage life of the tape in a temperate climate will be at least one year.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.