

## Scapa D210

D210 - Double Sided Polyester Tape - Differential rubber adhesives, Clean Removal, 0.07mm

---

### DESCRIPTION

Scapa D210 is a thin double sided tape based on a 23 micron polyester film coated on both sides with a rubber based adhesive system, protected with a 98 g/m<sup>2</sup> white paper release liner, with 0.07 mm total thickness. It is recommended for a variety of bonding, mounting and laminating applications where high plasticiser resistance is required.

### APPLICATIONS

- Temporary bonding of highly plasticised PVC mats on wooden varnished flooring or existing sports floor covering.

### PRODUCT BENEFITS

- Service temperature: -10°C to +70°C.
- Thin bonding solution.
- High shear resistance.
- Extreme plasticiser resistance.
- Clean removal (does not leave adhesive residue).

## TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesion to Steel - Open Side	2.2	N/cm	AFERA 5001
Adhesion to Steel - Liner Side	4.5	N/cm	AFERA 5001
Adhesive Thickness - Open Side	0.015	mm	AFERA 5006
Adhesive Thickness - Liner Side	0.035	mm	AFERA 5006
Total Thickness (excluding liner)	0.07	mm	AFERA 5006

## STANDARD PRESENTATIONS

- Colours: Transparent
- Core: 76mm Scapa branded cardboard
- Packaging: Bulk
- Roll Length: 45 metres
- Roll Width: 96 mm and 1360 mm

## RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. The product should be stored in temperatures between +10°C and +30°C. Under these conditions, the storage life of the tape in a temperate climate will be 12 months.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.