



Scapa T002

Medium Firm (MF1) Acrylic Adhesive Transfer Tape - 40 Micron, Neutral

DESCRIPTION

Scapa T002 is a 40 micron clear acrylic transfer tape coated onto an 80gsm yellow glassine release liner, recommended for splicing, laminating and product assembly applications.

APPLICATIONS

- Lamination on to wide variety of materials to make them self-adhesive.
- Flying splice of paper and cardboard.

PRODUCT BENEFITS

- Service temperature: -40°C to +150°C
- Good UV resistance and ageing properties.
- Adhesive contains glass fibres for easier converting.
- Acrylic adhesive combining good tack and peel adhesion with high cohesive strength.

Accreditation:

Acid free / pH neutral - compliant to ISO 18902. Photographic activity test (PAT) for enclosure materials - compliant to ISO 18916.

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesive Film Thickness	40	Microns	AFERA 5006
Peel Adhesion on Stainless Steel	6.5	N/25mm	AFERA 5001
Release Liner Thickness	67	Microns	AFERA 5006

 Version: 15
 Generated Date: 20 May 2024
 Page: 1 of 2

www.scapaindustrial.com Product Code: T002

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

STANDARD PRESENTATIONS

• Branding: neutral core

• Colours: Clear

• Core: 76mm cardboard

• Roll Length: 33 and 50 metres

• Roll Width: 12, 19, 25, 50 and 1,320mm

Note:

19mm x 55 metres also available

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C. Under these conditions, we recommend to use the product within 12 months from the date of manufacture.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.

 Version: 15
 Generated Date: 20 May 2024
 Page: 2 of 2

www.scapaindustrial.com Product Code: T002