

Scapa 2210

Coloured UPVC Packaging Adhesive Tape

DESCRIPTION

Scapa 2210 is a 33 micron coloured UPVC film coated with a white rubber/resin solvent based adhesive system, with 51µ total thickness and recommended for general packaging and colour coding applications.

APPLICATIONS

- Bag sealing.
- Box sealing.
- Bundling.
- Colour coding.
- Suitable for a variety of medium to light domestic packaging and sealing applications at home or in the office.

PRODUCT BENEFITS

- Easy unwind.
- Moderate tack.
- Moisture and chemical resistant.
- Printable.
- Shiny colour.
- Applicable by hand or with Scapa HD209 or HD210 dispensers.
- Continuous temperature resistance: +60°C.

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesion to Steel	2	N/cm	AFERA 4001
Elongation at Break	60	%	AFERA 4005
Tensile Strength	48	N/cm	AFERA 4004
Total Thickness	0.051	mm	AFERA 4006

STANDARD PRESENTATIONS

- Colours: red
- Core: 76 mm cardboard core
- Packaging: Flat shrink pack
- Roll Length: 66 metres
- Roll Width: 50 mm

Note:

19mm wide is available in plain (neutral) branding and subject to minimum order quantity.

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C. Under these conditions, the storage life of the tape in a temperate climate will be at least one year.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.