

Scapa 9001S

24-Hour General Purpose Masking Tape - Indoor Use

DESCRIPTION

Scapa 9001S is a 0.10mm semi crepe paper tape coated with a rubber based adhesive system, recommended for general purpose indoor masking applications.

APPLICATIONS

- Light weight bundling.
- Professional painters and plasterers masking tape for indoor use.
- Suitable for brush, roller and spray applications. Drying in room temperature condition.
- Suitable for general purpose indoor bonding, holding, sealing and masking applications (24 hours).

PRODUCT BENEFITS

- Interior application only.
- Clean removal at room temperature.
- Smooth and controlled unwind.
- Good peel adhesion.
- Good shear and holding strength.
- Good paint flake resistance.
- No staining.
- Resistant to mild chemicals, lacquers, solvents and water.

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesion to Steel	2.5	N/cm	AFERA 5001
Elongation at Break	8	%	AFERA 5004
Tensile Strength	35	N/cm	AFERA 5004
Total Thickness	100	Microns	AFERA 5006

Version: 12

Generated Date: 17 May 2024

Page: 1 of 2

www.scapaindustrial.com

Product Code: 9001S

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

STANDARD PRESENTATIONS

- Colours: Natural
- Core: 76mm Scapa branded cardboard core
- Packaging: Concertina
- Roll Length: 50 metres
- Roll Width: 18, 25, 30, 38, 50, 75 and 100mm

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C. Under these conditions, the storage life of the tape in a temperate climate will be at least one year.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.

Scapa masking tapes are not suitable for outdoor exposure and should not be submitted to prolonged periods of sunlight, as tapes may become difficult to remove. Clean removal may also vary with surface type, lacquers, primers and paints nature and the temperature of the surface at removal. For best results, remove the tape as soon as possible after applying the paints pulling it slowly at a 45° angle with constant speed.